

				HD 7/122	HD 10/122, HD 9/80, HD 12/130	K 1132, K 1152 TS T	K 2160 TS T, K 2175 TS T	K 2195 TS T	Profi 160 TS T, Profi 175 TS T	Profi 195 TS T	Profi 15/120 TS T	quadro 11/140 TS T, 12/150 TS T	quadro 9/170 TS T	quadro 599 TS T	quadro 899 TS T	quadro 800 TS T	quadro 1000 TS T	quadro 1200 TS T	quadro 1500 TS, 1500 TS T	D 30/180 TS T	D 26/250 TS T	Profi-Jet B 13/150, B 16/220	Profi-Jet B 10/200	Profi-Jet B 20/220	Profi-Jet B 16/250	B 170 T, B 240 T	B 200 T, B 270 T	B 230 T	therm CA 11/130 - 12/150	therm CA 15/120	therm C 11/130 - 13/180	therm C 15/150	therm 635-1, 875-1, 895-1	therm 1165-1	therm 1525-1
--	--	--	--	----------	-------------------------------	---------------------	--------------------------	-------------	--------------------------------	----------------	-------------------	---------------------------------	-------------------	-----------------	-----------------	-----------------	------------------	------------------	---------------------------	---------------	---------------	------------------------------	--------------------	--------------------	--------------------	------------------	------------------	---------	--------------------------	-----------------	-------------------------	----------------	---------------------------	--------------	--------------

Vario-Jet a plochá tryska s trubicou z ušlechtilé oceli a s možností regulace



Tryska Vario-Jet 03 500 mm  Č. výr. 41.156 8-03

Tryska Vario-Jet 042 500 mm  Č. výr. 41.156 8-042

Tryska Vario-Jet 055 500 mm  Č. výr. 41.156 8-055



Tryska M20042 500 mm  Č. výr. 12.701-M20042

Rotační keramická tryska s trubicou z ušlechtilé oceli

- max. 15 l/min
- max. 185 barů
- max. 70 °C



Tryska 028 500 mm  Č. výr. 41.570-028

Tryska 03 500 mm  Č. výr. 41.570-03

Tryska 042 500 mm  Č. výr. 41.570-042

Tryska 045 500 mm  Č. výr. 41.570-045

Tryska 055 500 mm  Č. výr. 41.570-055

Tryska 07 500 mm  Č. výr. 41.570-07

Tryska 035 600 mm  Č. výr. 46.150

Tryska 045 600 mm  Č. výr. 46.150 1

Tryska 055 600 mm  Č. výr. 46.150 3

Tryska 06 600 mm  Č. výr. 46.150 2

Rotační keramická turbo tryska s trubicou z ušlechtilé oceli

- max. 25 l/min
- max. 250 barů
- max. 80 °C



Tryska 04 600 mm  Č. výr. 41.072

Tryska 045 600 mm  Č. výr. 41.072 3

Tryska 05 600 mm  Č. výr. 41.580-05

Tryska 055 600 mm  Č. výr. 41.072 4

Tryska 07 600 mm  Č. výr. 41.072 7

Tryska 08 600 mm  Č. výr. 41.072 8

Tryska 10 600 mm  Č. výr. 41.580-10

Tryska 11 600 mm  Č. výr. 41.580-11

Vysokotlaké čisticí přístroje - příslušenství

Injektory pro čisticí prostředky



s trubice z ušlechtilé oceli, regulační tryska 028

Č. výr. 13.376 7

HD 7/122

HD 10/122, HD 9/80, HD 12/130

K 1132, K 1152 TS T

K 2160 TS T, K 2175 TS T

K 2195 TS T

Profi 160 TS T, Profi 175 TS T

Profi 195 TS T

Profi 15/120 TS T

quadro 11/140 TS T, 12/150 TS T

quadro 9/170 TS T

quadro 599 TS T

quadro 799 TS T

quadro 899 TS T

quadro 800 TS T

quadro 1000 TS T

quadro 1200 TS T

quadro 1500 TS T

D 30/180 TS T

D 26/250 TS T

Profi-Jet B 13/150, B 16/220

Profi-Jet B 10/200

Profi-Jet B 20/220

Profi-Jet B 16/250

B 170 T, B 240 T

B 200 T, B 270 T

B 230 T

therm CA 11/130 - 12/150

therm CA 15/120

therm C 11/130 - 13/180

therm C 15/150

therm 635-1, 875-1, 895-1

therm 1165-1

therm 1525-1



s trubice z ušlechtilé oceli, regulační tryska 042

Č. výr. 13.376 6

Pěnové injektory



- max. 250 barů
- max. 80 °C
M 22 vnější závit, 1 l

Č. výr. 13.390 1



- max. 250 barů
- max. 80 °C
M 22 vnější závit, 2 l

Č. výr. 13.390 2



- max. 250 barů
- max. 80 °C
Rychlospojkový trn, 1 l

Č. výr. 13.391 1



- max. 250 barů
- max. 80 °C
Rychlospojkový trn, 2 l

Č. výr. 13.391 2



CleanBoy 1,25 l



Č. výr. 41.299 1

